

GARBAGE COLLECTION USING SMARTBIN

Chaitra. S Muttali¹, Architha. S C², Bhumika. K³, Haripriya. R⁴ & N. Guruprasad⁵

^{1,2,4,5}Research Scholar, Department of Computer Science & Engineering, Global Academy of Technology, Bengaluru, India

³Professor, Department of Computer Science & Engineering, Global Academy of Technology, Bengaluru, India

ABSTRACT

The main idea in good pickup of the camera is that they are placed at the side of load cell sensing element of garbage bin. The camera can take continuous pictures of the bin. A threshold is set, that is compared with the output of camera and cargo sensing element, this comparison is assisted with the help of microcontroller. When analyzing the image one can tend to get a plan concerning the amount of the garbage present within the bin and also with the help of load cell sensing element one can tend to get understand the burden of garbage, data is processed and the microcontroller checks if the threshold level is exceeded or not, it then sends a message through GSM module to apprise that the bin has crossed its capability, and the garbage disposal is needed. So that the specified authority sends the vehicle for clearing the bin

KEYWORDS: Smart bin, Garbage

Article History

Received: 26 Mar 2020 / Revised: 02 Apr 2020 / Accepted: 16 Apr 2020

INTRODUCTION

As our nation is in the stage of development, there is one problem where all have to deal with it. In day to day life, one can see that the bins being overflowing, results in the increased amount of diseases, and the absence of good environment. A huge task is disposal of the waste. Here, such a system needs to be introduced which may reduce the problem. This system gives us one of the best efficient ways to keep our environment clean.

Smart waste management is a key idea to control these problems. Smart bins play a major role in preventing the overflow of the garbage thereby preventing widespread of diseases. The vehicle for collecting the garbage will have to be frequently used to empty the bin. So the problem of overflowing can be prevented.

Then comes the last part, which is the disposal of the garbage - to overcome the overflowing of the waste, where the garbage disposal system is made completely automatic. There will be two separate smart bins for garbage collection, one for biodegradable waste that is wet waste and another one for non-biodegradable waste that is dry waste. As soon as the threshold level crosses in any of the bins, that information will be sent to the respective municipal office through an android application.

To become a developed country it's time that one should always use technology for waste management systems. So, in this paper there is an integration of analytics and electronics to make changes with the conventional method of waste collection.

Proposed System

There should be digitalized way to make compatible to the current technologies with relatively low cost. So, the best way is to form an IOT system where all the operations will be automatic which improve the technique of collecting the waste for the bin by adding some sensors to check the level of waste in the bin. A route optimization algorithm will be used to optimize the path of the tracks, and the bins to be discharged. By implementing the cost required, and the time taken to empty the bins will be reduced.

Scope of the Project

Manually controlled activities take time to complete the task and also there will be a stinking problem. So, we can incorporate the odor control mechanism to reduce foul smell of organic garbage. Also, the requirement of smart dustbin, GPS module can be used for path optimization along with ultrasonic sensor.

Design Overview

Each waste bin is given variety id which will be stored in the respective database with its location. A camera will be placed at each smart bin, the camera used is INTEX IE305WC which is used for taking snapshots of waste bin. Database will be maintained for each smart bin and various threshold levels will be set depending on the analysis of the previously taken snapshots. One weighing sensors is used which consists of one point load cell of precision C3 class and is made from aluminum alloy which can sense the weight of the smart bin which will be interfaced with the microcontroller through ADC. The microcontroller present in the smart bin compares the threshold value with the data generated if the data value is exceeded than the threshold value. Then, a message is sent through the GSM module to the server. The message consists of the id of the smart bin. Server then compares the id with its database.

After receiving the message the server will send the vehicle to dispose the waste and empty the can to the specified location. Later, the driver enters the password with help of keypad in microcontroller. And, when the password matches robot mechanism is activated. In this robot mechanism, machine capable of physical motion that is during the disposal process one can use dc motor which will be fixed on plate on which the smart bin will be mounted. This plate will tilt, and the garbage will be disposed to the vehicle.

System Architecture

System is divided into three different layers:

- **Dustbin layer:** This layer is nothing but a smart bin implemented in different locations for garbage collection which will be connected to the server.
- **Server layer:** Server layer is the one to which the message will be sent from the smart bin for the disposal of the garbage.
- **Client layer:** Clients ask for the nearest smart bin enabled dustbin will be processed by the server.




Figure 1

Software Requirements

- **Kiel Software:** The KEIL C51 C compiler for the 8051 microcontroller is the most popular 8051 C compiler. The C51 compiler translates the C source files into relocatable object modules which contain full symbolic information for debugging with an in-circuit emulator.
- **Embedded C:** Embedded C is a set of language extensions for the C programming language by the C Standards Committee to address commonality issues that exist between C extensions for different embedded systems.
- **Flash Magic:** Flash Magic is a tool for programming flash-based micro controllers from NXP employing a serial or Ethernet protocol while within the hardware.

Hardware Components

- **Power supply:** It won't provide DC voltage to the components used. It supplies 12V of current for DC motor, 3.3V of current for microcontroller and 5V of current for others.
- **Web camera:** Camera is placed above the garbage and can take snapshots of the garbage present in it, so as to know on which extent the bin is filled. A webcam also acts like a video camera. When the data sent is sent to the server to a remote location, the video stream may be viewed or saved.
- **Load Sensor:** Load sensor will be placed below the garbage and can sense the weight of garbage present in it. This will give continuous weight readings in voltage format, which is then given to the microcontroller. The microcontroller then converts the signal from analog to digital format.
- **Microcontroller:** Microcontroller is used to process the data that is been given by the sensors as in input to the microcontroller. It compares the received data with the threshold level initially set and accordingly the output will be generated. LPC2131/32/34 microcontroller's supports 16/32-bit ARM7TDMI- S CPU with real-time emulation and embedded trace support, that combine the microcontroller of high- speed non-volatile storage.
- **LCD (Liquid Crystal Display):** LCD is employed to see the output generated. One can use 16x2 LCD. So that, one can write 16 characters in each line - totally 32 characters can be displayed. LCD plays a major role as the output will be displayed on it and to debug the system in simplified way, that is, module wise whenever the system fails.

- **GSM Module:** It won't send message to the respective authority if the bin is filled and exceeds the threshold value. Through, GSM module, one can send short text messages to the specified authorities.

Implementation and Methodology

Each smartbin will be given variety id which will be stored in the specific server database with its location. A camera will also be placed at each bin. The camera used is INTEX IE305WC which is a 16 megapixel camera used for capturing the snapshots of the bin. This is will adopted along with the microcontroller. And also a weighing sensor is used to weigh the amount of garbage present in the bin which is made up of Aluminum Alloy. This will be adopted along with the microcontroller through ADC.

Whenever the input is fed into the microcontroller, it compares default threshold level set initially, if the data exceeds the threshold level, then the microcontroller which will be interfaced with GSM module sends a message to the server which contains the id of the smart bin. Later, the server compares with its database and if it matches, vehicle will be sent to the location by implementing route optimization algorithm to clear the bin.

Flowchart




Figure 2

Circuit Diagram

The hardware components used are PIC16F73 microcontroller, HC-SR04 ultrasonic sensor, SIM900A GSM module, IC7805 voltage regulator, resistor, capacitor and a crystal oscillator. PIC16F73 is a CMOS-FLASH based 8 bit microcontroller along with that, it has got two 8 bit and one 16 bit timer/counter. Microcontroller will also be additionally interfaced with Tx and Rx pin for serial communication. Those pins will be connected to the GSM module through the inbuilt MAX 232IC present in the module. MAX 232IC serves to convert the logic from TTL to RS232 logic, as the GSM module operates at RS232 while PIC16F73 microcontroller at TTL logic. The circuit diagram is shown below in the diagram.

The ultrasonic sensor consists of two pins: Trigger pin and Echo pin used for calculating the time duration of the echo that is generated. Initially a high to low signal by the microcontroller at the trigger pin of the sensor sends eight 40 kHz sound waves, after which the ECHO pin is turned high until echo of the sound waves echoed back to the sensor.




Figure 3

As lots of bins will be present in each locality - the garbage collecting vehicle collects the waste from these bins. The dustbin will be divided into three different levels according to the extent of garbage filled in the smart bin.

The following variables used in route optimization algorithm:

- $i, k = 1, 2, \dots, n$, unique ID given to the n number of smart-bins L_i = Current level of the i th smartbin.
- t_i = time taken for the i th bin to be filled.
- ak_1 = Average time of k th smartbin to urge filled.
- $T_k[L_k, t_k]$ = Array which consists the last updated level and time of each smartbin within the network.

Result: Predicted percentage filled status of each smart-bin and thus estimate the optimal route supported potential filled Bins.

Use Case Diagram




Figure 4

SMS received from the GSM modules of the dustbins is taken in the sort of text files. These text file will be connected to the excel sheets.

CONCLUSIONS

In this method of smart waste management using Internet of Things (IoT) with the help of ultrasonic sensor to check the status of the smart bins, where two smart bins will implemented for biodegradable waste that is wet waste another for non-biodegradable waste that is dry waste. As soon as the threshold level is crossed, a message will be sent to the specific authorities regarding the smart bin to clearance of the bin so to avoid overflowing of garbage. The local people can also request the authorities for the additional smart bins if required. As, all the operations happening within the smartbins are updated, the chances of breakdown of the smart bin will be reduced.

REFERENCES

1. "Smart Garbage Collection System in residential area", Gaikwad Prajakta, Jadhav Kalyani, Machale Snehal, *IJRET*, Mar-2015.
2. "Smart Bin Implementation for Smart Cities", Narayan Sharma, Nirman Singha, Tanmoy Dutta, *International Journal of Scientific & Engineering Research*, 6,9, September-2015.
3. "Garbage monitoring and disposal system for smart city using IOT", Dr. Prasun Chowdhury, RittikaSen, Dhruva Ray, Purushottam Roy and Souradeep Sarkar, *Second International Conference on Green Computing and Internet of Things (ICGCIoT)*.