

## **IMAGE TRANSFER USING MODIFIED D2D OF 5G TECHNOLOGIES IN ADHOC NETWORK**

**Senan Ali Abd<sup>1</sup>, Manjunath. S. S<sup>2</sup> & Sayed Abdulhayan<sup>3</sup>**

<sup>1</sup>MCA Department, Dayananda Sagar Institutions, Bangalore, India

<sup>2</sup>IS Department, Dayananda Sagar Institutions, Bangalore, India

<sup>3</sup>Telecommunication Department, Dayananda Sagar Institutions, Bangalore, India

### **ABSTRACT**

*D2D (Device-to-Device) communication is being used for the transfer of Image from source to destination. D2D is the 5G technology used for stable Networks. Here we are using the same D2D technology for Adhoc Network, wherein we are assuming the Device components are roaming and changing their position with respect to time. In this transaction, we will get to know about the performance of D2D technology in Adhoc Networks.*

**KEYWORDS:** D2D (Device-to-Device), 5G (5th Generation Communication Technology), UL(Uplink), DL(Downlink), SL(Side Link), EUTRAN(Evolved Universal Terrestrial Radio Access), EPC (Evolved Packet Core)

---

### **Article History**

**Received: 20 Apr 2018 / Revised: 13 Jun 2018 / Accepted: 25 Jun 2018**

---